

# Boost Performance

With a Cost-Effective Variable Speed Pump Solution

## PRODIGY SERIES

End Suction - Centrifugal Pumps

The Prodigy Series is a highly compact, customizable package designed for **HIGH FLOW – LOW BOOST** applications. It features **NSF 61** Rated, **304 S.S.** End Suction pumps with **304 S.S.** casing and impeller. All controls are protected within a **UL Type 2** forced-air ventilated enclosure with inlet filter and **UL Type 4x** active incoming surge suppressor with LED indicator.

iQFlo<sup>3.0</sup>

### Integral to All Systems

- **iQFlo™ 3.0** Award-Winning Variable Speed B.O.S.S. (Booster Operating System Software)
- **GreenFlo™** ASHRAE/ANSI/IES Standard 90.1 Compliant Low-Flow Energy Optimization Algorithm



### Prodigy Features

- **5 Year Limited Warranty** on the entire 3rd party certified system
- **304 Stainless Steel** headers and square tube space frame
- **Standard 100,000 SCCR Controller Rating** at incoming disconnect
- **NSF 61 and NSF 372 System Compliance** (N-5946/7626 IAPMO)
- **7" TFT Full Color Touch Screen** interface with easy-to-follow wizards
- **Vertically Mounted End Suction Pumps** for ease of service and maintenance
- **Small Footprint** for retro-fit simplicity
- **Simplex, Duplex, Triplex and Quadraplex** systems available in a multitude of voltages/horsepowers

**EXPLORE THE DYNAMICS  
OF THE PRODIGY SERIES  
WITH A FREE CONSULTATION**



  
**QuantumFlo**  
A WILCO BRAND



**wilo**

QuantumFlo, A Wilo Brand, 2664 Jewett Lane, Sanford, FL 32771  
407-807-7050 | QuantumFlo.com | QFlo.Support@Wilo.com | Linktr.ee/QuantumFlo